



IP
COMPACTOR

PRODUCT OPTIONS AND ACCESSORIES

- S56/060 Lift-A-Pak Bag Lifter for IP400/IP500/IP600/IP700 Waste Compactor

With a 55-litre equivalent uncrushed capacity, the Impactor IP400 allows operators to cut waste volumes by up to 80%. It saves on staff time, reduces collection costs, improves hygiene standards and minimises space needed for waste storage.

The IP400 is suitable for a wide variety of operations, from small hotels and restaurants to large schools, hospitals, shops, factories and ships. From cardboard and tins, to plastic and paper, it compacts waste in seconds using powerful electro-hydraulic technology.

The unit is compact and mounted on heavy duty

PRODUCT FEATURES

- Cuts waste volumes by up to 80% and lowers waste handling and collection cost
- Compresses all dry waste - cardboard, tins, plastic and paper
- Powerful electro-hydraulic technology enables waste to be compacted in seconds
- Compact, easy-to-move unit can be conveniently located where waste is produced
- Manufactured from stainless steel making it tough, reliable and easy to clean
- UK 3 pin plug allows users to simply plug in and switch on

AIA FILE NUMBER:

ITEM NUMBER:



WEIGHTS & DIMENSIONS

Width	580 mil
Depth	566 mil
Height	1645 mil
Weight	222.5 kg

SHIPPING DETAILS

Ship Width	70 cm
Ship Depth	64 cm
Ship Height	180 cm
Ship Weight	244.75 kg
Number of Shipment Parcels	1
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

WATER, PLUMBING, AND DRAINAGE SPECS

Water Line Required	No
Drain Line Required	No

PRODUCT CERTIFICATIONS

UK
CA IP55

ENERGY SPECS

Primary Energy Type	Electric
Electrical Total Amperage	5 A
Electrical Volts	230V
Electrical Total Wattage	750 W
Electrical Kilowatts	0.75 kW
Electrical Phase	1-Phase

Electrical Plug Type	UK 3-Pin Plug
Number of Electrical Plugs	1
Electrical Connection Type	Cord and Plug
Number of Electrical Conductor Wires	1
Dedicated Circuit Required	No
Electrical Remarks	Single

ADDITIONAL SPECIFICATIONS

Capacity Volume	55 l
Construction Materials	Stainless Steel
Control Type	On/Off, Rotary Control Knob
Equivalent Uncrushed Material	275 l
Operator Safety Method	Interlock
Self-Cleaning Capable	No
Waste Compaction Ratio	80 %
Waste Types Processed	Dry (cardboard, tins, plastic, paper)



BIDDING SPECIFICATIONS

Bidding Specifications Not Available.

TECHNICAL DRAWING